

## Model 200 Load Switch



## Model 204 Flasher



The commitment to quality and reliability found in EDI Signal Monitors continues with the Model 200 solid state Load Switch and Model 204 solid state Flasher.

The heavy duty extruded aluminum heat sink chassis of the Model 200 and 204 is designed to allow the triac device to operate with the full load current at high temperature (+74°C) without exceeding the manufacturer "Maximum Allowable Case Temperature" triac device specification. This helps ensure long life and reliable operation from the triac device. It can be shown that device reliability is logarithmically related to device operating temperature.

### Model 200 Operational Features

- ✓ Meets NEMA TS1, TS2, and Type 170 requirements.
- ✓ 10 Amp RMS Maximum Load Current over full NEMA temperature range of -34°C to +74°C
- ✓ Operating Voltage Range: 60 to 135 VAC
- ✓ Zero crossing: Less than 5 degrees of zero voltage point
- ✓ Isolation greater than 2000 volts
- ✓ Off state leakage less than 10 mA peak
- ✓ Maximum input current less than 20 mA
- ✓ Peak Inverse Voltage: 600V
- ✓ One cycle surge: 250 A peak.
- ✓ Noise rejection is greater than  $\pm 300V$  peak
- ✓ Three electrically independent circuits
- ✓ Dimensions: L = 8.025" x H = 4.170" x W = 1.475"

### Model 204 Operational Features

- ✓ Meets NEMA TS1, TS2, and Type 170 requirements.
- ✓ 15 Amp RMS per circuit Maximum Load Current over full NEMA temperature range of -34°C to +74°C
- ✓ Operating Voltage Range: 60 to 135 VAC
- ✓ Zero crossing: Less than 5 degrees of zero voltage point
- ✓ Dual Circuit Operation
- ✓ Provides 56 Flashes/Minute
- ✓ MOV protection on outputs
- ✓ Peak Inverse Voltage: 600V
- ✓ One cycle surge: 250 A peak.
- ✓ Noise rejection is greater than  $\pm 300V$  peak
- ✓ Dimensions: L = 8.025" x H = 4.170" x W = 1.475"

### EBERLE DESIGN INC.

3510 East Atlanta Avenue  
Phoenix, AZ 85040 USA  
www.EDITraffic.com

Tel (480) 968-6407  
Fax (602) 437-1996



