

# PS-175-12

## Heavy Duty Rack Power Supply Operations Manual

THIS MANUAL CONTAINS TECHNICAL INFORMATION FOR THE  
PS-175-12 SERIES POWER SUPPLY.

REVISION: AUGUST 2016  
pn 888-0175-004



EBERLE DESIGN INC.

3510 East Atlanta Avenue  
Phoenix, AZ 85040 USA  
www.EDIttraffic.com

Tel (480) 968-6407  
Fax (602) 437-1996



THE PS-175 SERIES POWER SUPPLY IS DESIGNED AND MANUFACTURED IN THE  
USA BY EBERLE DESIGN INC.  
PHOENIX, ARIZONA  
EDI IS CERTIFIED TO ISO 9001:2008 QUALITY SYSTEMS STANDARDS.

INFORMATION CONTAINED HEREIN IS PROPRIETARY TECHNICAL INFORMATION  
OF EBERLE DESIGN INC. PUBLICATION, REPRODUCTION OR USE IN WHOLE OR  
PART IS NOT PERMITTED EXCEPT UNDER TERMS AGREED UPON IN WRITING.

© COPYRIGHT 2016 EDI

## 1.1 OVERVIEW

The PS-175-12 Rack Power Supply is a rack mounted high efficiency switching power supply that provides four independent channels of regulated 12 VDC power for a NEMA TS-1 Detector Rack. The PS-175-12 meets or exceeds all requirements of the NEMA Standard TS-1 1989 R2000. The AC Line input is rated for universal 89 to 270 Vac operation, 50/60 Hz.

## 1.2 OUTPUT CONFIGURATION

The PS-175-12 provides four independent regulated outputs each rated at 1.25 Amps over the full -30°F to 165°F (-34°C to +74°C) NEMA operating temperature range. Each output is fused for over-current protection. Each output is also protected against voltage transients by a 1500 Watt suppressor.

## 1.3 INDICATORS

A separate green LED indicator is provided to display output status and fuse integrity for each of the four supply outputs.

## 1.4 ELECTRICAL

### 1.4.1 POWER REQUIREMENTS

AC Operating Voltage Minimum ..... 89 Vac  
 AC Operating Voltage Maximum ..... 270 Vac  
 AC Operating Frequency ..... 45 to 65 Hz  
 Fuse (5mm x 20mm) ..... 3.15A Slow Blow

### 1.4.2 DC OUTPUTS

DC Output Voltage ..... 12 Vdc +/- 10%  
 DC Output Voltage Maximum (no load) ..... 16.0 Vdc  
 DC Output Current Maximum (per channel)..... 1.25 Amps  
 Fuse (6.35mm x 31.75mm)..... 2A Slow Blow

### 1.4.3 MECHANICAL

Height..... 4.5 inches  
 Width..... 2.0 inches  
 Depth (excluding handle)..... 6.875 inches

### 1.4.4 ENVIRONMENTAL

Storage Temperature Range ..... -45 to +85 °C  
 Operating Temperature Range ..... -34 to +74 °C  
 Humidity (non-condensing)..... 0 to 95% Relative

## 1.5 MAIN CONNECTOR

The main connector is a double sided 44 pin edge type with 0.156 inch center gold fingers.

Pin	Pin	Function
A	1	DC Common
B	2	Channel 1 DC Output
C	3	Channel 2 DC Output
L	10	Chassis Ground
M	11	AC Neutral
N	12	AC Line
U	17	Channel 3 DC Output
V	18	Channel 4 DC Output

All other pins are not connected