

PS200-225

Nema TS-2 Cabinet Power Supply Operations Manual

THIS MANUAL CONTAINS TECHNICAL INFORMATION FOR
THE PS200-225 SERIES CABINET POWER SUPPLY.

REVISION: NOVEMBER 2014
pn 888-0200-002



EBERLE DESIGN INC.

3510 East Atlanta Avenue
Phoenix, AZ 85040 USA
www.EDIttraffic.com

Tel (480) 968-6407
Fax (602) 437-1996



THE PS200 SERIES POWER SUPPLY IS DESIGNED AND MANUFACTURED IN THE
USA BY EBERLE DESIGN INC.
PHOENIX, ARIZONA
EDI IS CERTIFIED TO ISO 9001:2008 QUALITY SYSTEMS STANDARDS.

INFORMATION CONTAINED HEREIN IS PROPRIETARY TECHNICAL INFORMATION
OF EBERLE DESIGN INC. PUBLICATION, REPRODUCTION OR USE IN WHOLE OR
PART IS NOT PERMITTED EXCEPT UNDER TERMS AGREED UPON IN WRITING.

© COPYRIGHT 2014 EDI

1.1 OVERVIEW

The PS200-225 Cabinet Power Supply is a shelf mounted high efficiency switching power supplies that provide regulated DC power, unregulated AC power, and a line frequency reference for the BIUs and other auxiliary equipment. The PS200 meets and/or exceeds all requirements of the NEMA TS2-2003 (R2008) Standard.

The PS200-225 product is designed to operate from a 220 Vac 50 Hz or 220 Vac 60 Hz nominal AC Mains source.

All TS-2 Type 1 cabinet assemblies require the use of a cabinet power supply unit as well as any TS-2 Type 2 cabinet assemblies that utilize Bus Interface Units (BIU). The PS-250 model is intended for high power in the detector rack for devices such as video detection and provides 5 Amps at 12 Vdc.

1.2 INDICATORS

A separate LED indicator is provided to display output status and fuse integrity for the two DC supply outputs and the 12 VAC output. The Line Frequency Reference indicator pulses to show 50/60 Hz activity.

1.3 SPECIFICATIONS

1.3.1 POWER REQUIREMENTS

AC Operating Voltage Minimum 160 Vac
AC Operating Voltage Maximum 270 Vac
AC Operating Frequency 45 to 65 Hz

1.3.2 DC OUTPUT

24VDC Output Voltage 24 Vdc +/- 2 Vdc
24VDC Output Current Maximum 2 Amps
12VDC Output Voltage 12 Vdc +/- 1 Vdc
12VDC Output Current Maximum (PS200) 2 Amps
12VAC Output Voltage Minimum (At AC Line = 196Vac) 7.5 Vac
12VAC Output Current Maximum 0.25 Amps
Minimum Holdup Time 50 milliseconds

1.3.3 MECHANICAL

Height 5.3 inches
Width 4.0 inches
Depth (including connector) 8.3 inches

1.3.4 ENVIRONMENTAL

Storage Temperature Range -45 to +85 °C
Operating Temperature Range -34 to +74 °C
Humidity (non-condensing) 0 to 95% Relative

1.4 MAIN CONNECTOR

The main connector mates with an MS3106()-18-1SW or equivalent.

Pin	Function	Pin	Function
A	AC Neutral	F	Reserved
B	Line Frequency Reference	G	Logic Ground
C	AC Line	H	Earth Ground
D	+12 Vdc Output	I	12 Vac Output
E	+24 Vdc Output	J	Reserved