



MMU16-EXT-CARD

DIP SWITCH ENABLED PROGRAM CARD FOR EDI NEMA MONITORS

Designed to facilitate cabinet testing when multiple Program Card configurations are needed.

FEATURES

- Twin 96 pin DIN connectors
- Compatible with any EDI MMU meeting the requirements of Nema TS2-2003
- DIP switches for all programmable functions

HIGHLIGHTS

- DIP switches replace the need for soldered wire jumpers and make modifications to the MMU set-up fast and easy
- Intended for cabinet test use only and is not designed or provided for on-street use



Connector

Twin 96 pin DIN connectors compatible with any MMU meeting the requirements of Nema TS2-2003, including the MMU-16E and MMU-16LE models.

Programmable Functions

DIP Switches replace the need for soldered wire jumpers for the following functions: Permissive Matrix, Minimum Flash, Minimum Yellow Change Disable, 24V & CVM Latch Enable, Program Card Ajar Test.

Program Card Memory

The MMU-16LE SmartMonitor® memory feature is supported.

Dimensions

PCB Width: 8.0 inches (Handle adds 1" to Width). PCB Height: 7.75 inches.

Cabinet Test Use Only

This product is intended for cabinet test use only and is not designed or provided for on-street use.



Specifications subject to local environmental conditions, and may be subject to change. All Eberle Design LLC. products are Designed, Manufactured and Tested in the United States of America in facilities that are certified to ISO quality standards. "Eberle Design Inc." and "Eberle Design LLC." logo are trademarks of Eberle Design Inc. ©2024, Eberle Design LLC. Document: EDI_DATA_MMU16-EXT-CARD_RevA